


LED Tri-proof Batten proline 36W 900mm (3ft)



DIMENSIONS



LIGHT DISTRIBUTION CURVE



KEY DATA

Power	36W
Luminous Flux	4800lm
Colour Temperature	3000K/4000K/6500K
IP Rating	IP 65
Dimensions	900x115x62mm
Warranty	5 Years Extended

Part Number 3000K

CL-TP-BN90-135-36W-WW

Part Number 4000K

CL-TP-BN90-135-36W-NW

Part Number 6500K

CL-TP-BN90-135-36W-CW

TECHNICAL SPECIFICATIONS

Input Voltage	100~240Vac
Power Factor	>0.9
Warm white(2700-3000K)	4160lm
Natural white(4000-4500K)	4500lm
Cold white(5800-6500K)	4800lm
LED Manufacturer	Epistar
LED Type	SMD2835
No. of LEDs	180
Luminous Efficacy	135lm/W
Driver Manufacturer	Lifud/AGT
Total Circuit Power(W)	36W+/-5%
Electrical Class	II
Colour Rendering	>80 CRI
Lamp Viewing Angle	120°
Dimmable(option)	Dali/0-10V/PWM
Operating Temp.	-25°C to +50°C
Lifespan	55,000 Hours
Diffuser Material	Polycarbonate
Housing Material	Aluminium
Flickering free	Yes
Weight	1.8Kg

Application




Metro station



Airport



Indoor Carpark



Natorium



Warehouse



Production hall